Specialty Materials

A FULL LINE OF DIGITAL PRINTING AND PLOTTER CUT FILMS FOR TEXTILE DECORATION

ColorJET Media

Introducing 3 new materials to our line of digital-print heat-press media



CJM-2265 Solvent Matte

True matte finish available in 24" and 50" widths. Prints with all solvent/ecosol printers.

Make sure that the print is thoroughly dry before masking!



Applies to most cotton and blended fabrics.



Print and cut this material "right-reading"



370°F



Use our TM-854 Clear Transfer Mask to remove image from paper backing and transfer image to the garment.



Firm, even pressure.



15-20 seconds



Peel Cold



Wash inside-out. Gentle cycle, cold. Tumble dry.



CJM-2275 Multi-Ink Dark

For dark colored materials. Available in 17", 24" and 50" widths. Printable using Solvent, Aqueous and Pigmented inks.

Make sure that the print is thoroughly dry before masking!



Applies to most cotton and blended fabrics.



Print and cut this material "right-reading." Trim excess white from design.



°F C

Use our TM-854 Clear Transfer Mask to remove image from paper backing and transfer image to the garment.



Medium to firm even pressure



25 seconds



Peel Cold



Wash inside-out. Gentle cycle, cold. Tumble dry.



CJM-2285 Multi-Ink Light

For light and white colored materials. Available in 17", 24" and 50" widths. Printable using Solvent, Aqueous and Pigmented inks.



Applies to most cotton and blended fabrics.



Print and cut this material in mirror image



345°



Wash inside-out. Gentle cycle, cold. Tumble dry.



Medium pressure



30-40 seconds



Peel Cold

Check us out at www.SpecialtyMaterials.com

Please make sure this material is free from dust and debris before printing.

This can be accomplished by wiping material with a dry cloth.

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Technical Support Toll Free: 877-437-8556; Fax: 918-437-8588