

## **ColorPrint**<sup>™</sup>Standard

White CP-2100

Best all around product,

cuts the finest detail and prints the brightest colors

Designed for thermal transfer printing and computer plotter-cutting.

Transfers to most cotton and cotton-blend fabrics as well as some textured synthetics.

## **ColorPrint**<sup>™</sup>Nylon

Special adhesive for nylon garments

White CPN-2150

## **ColorPrint**<sup>™</sup>**Economy**

Paper-backed version of CP-2100 Standard.

White CPE-2110

Designed for use with all Eco-Solvent, Solvent, and Thermo Resin Inks.



Most cotton and cotton blend fabrics as well as some textured synthetics.



Hard, Even pressure



Print and cut this material "right-reading." Allow to dry 4-6 hours before weeding.



30 seconds



Use Transfer & Seal Tape to remove image from paper backing and transfer image to the garment.



Peel Cold



300°F - 315°F



Turn inside-out, cold water, tumble dry low.

## Check us out at www.SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Technical Support Toll Free: 877-437-8556; Fax: 918-437-8588