

GlitterFlex® ULTRA

- Easy to use pressure sensitive carrier for easy weeding
- Real glitter flakes encased in high quality heat sealing adhesive
- Great for adding value and making your designs stand out
- Pressure-sensitive carrier enables easy repositioning

					
Silver GF-Ultra 01	Gold GF-Ultra 02	Red GF-Ultra 03	Pink GF-Ultra 04	Purple GF-Ultra 05	Emerald GF-Ultra 06
					
Black Gold GF-Ultra 07	Jade GF-Ultra 08	Aqua GF-Ultra 09	Brown GF-Ultra 10	Black GF-Ultra 11	Blue GF-Ultra 12
					
Old Blue GF-Ultra 12A	Holo Pink GF-Ultra 13*	Light Green GF-Ultra 14	Multi GF-Ultra 15	Light Multi GF-Ultra 16	Grey GF-Ultra 17
					
Lavender GF-Ultra 18	Green GF-Ultra 19	Copper GF-Ultra 20	Dark Purple GF-Ultra 21	Navy Blue GF-Ultra 22	Light Gold GF-Ultra 23
					
Cherry GF-Ultra 24	Royal Blue GF-Ultra 26	Hot Pink GF-Ultra 27	Dark Green GF-Ultra 28	Burgundy GF-Ultra 29	Holo Orange GF-Ultra 30*
					
Dark Gold GF-Ultra 31	Sky Blue GF-Ultra 32	Silver Pink GF-Ultra 33	Light Purple GF-Ultra 34	Wine GF-Ultra 35	Orchid GF-Ultra 36
					
Rainbow Red GFU-RB 40	Rainbow Aqua GFU-RB 41	Rainbow Pink GFU-RB 42	Rainbow Dark Pink GFU-RB 43	Rainbow Light Green GFU-RB 44*	Rainbow Yellow GFU-RB 45*
					
Rainbow Silver White GFU-RB 46*	Rainbow White GFU-RB 47*	Neon Yellow GFU-Neon 50*	Neon Green GFU-Neon 51*	Neon Pink GFU-Neon 52*	Neon Red GFU-Neon 53*
					
Neon Orange GFU-Neon 54*	Neon Purple GFU-Neon 55*	Neon Blue GFU-Neon 56*	Holo Purple GFU-Holo 60	Holo Red GFU-Holo 61	Holo Blue GFU-Holo 62
					
Holo Green GFU-Holo 63	Holo Gold GFU-Holo 64	Holo Silver GFU-Holo 65	Holo Grey GFU-Holo 66		

* Starred colors are slightly translucent and will take on the color of the garment, especially on black or dark garments.

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS

LOVE what you PRESS!



Please note: If material starts to separate from the liner, just smooth it back down before cutting.

Application Instructions

Adheres to Cotton, Uncoated Polyester, Fabric blends, Wool, Linen



60° Blade



Cut this material
in mirror image



330°F - 335°F



Firm,
even
pressure



17 - 20
seconds



Peel warm, use
Teflon Sheet and
repress for 2 seconds



Wash inside out,
wash cool,
tumble dry

No nylon. Please be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.

We do not recommend this as a bottom layer material.

*Instructions for application to moisture-wicking materials:

Damp a cloth with rubbing alcohol (isopropyl alcohol), then rub it into the area on the garment you want to apply your design. Allow it to dry and apply your material. This will allow better adhesion to the garment.

*Instructions for application to dazzle cloth & shiny polyester fabrics:

We highly recommend that you TEST prior to doing large runs. Coated polyester can routinely cause adhesion issues.



Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

Copyright © 2014, Specialty Materials & Digital Decoration, LLC. All rights reserved. 2929 W. 21st Street, Tulsa, OK 74107